

BECKER HELIUM COMPRESSORS

Model	Electric Motor	Rotational Speed	Size Length/Depth/ Height (mm)	Flow Rate Litres Per Min	Final Compression Pressure Max	Pressure Levels	Cylinders
SV 125/40 He	3kW	1000 rpm	650mm / 495mm / 520mm	125 l/min	40 bar (580 psi)	2	2
SV 245/40 He	4kW	1500 rpm	650mm / 540mm / 560mm	245 l/min	40 bar (580 psi)	2	2
SV 500/40 He	9kW	1500 rpm	850mm / 640mm / 670mm	500 l/min	40 bar (580 psi)	2	2
SV 1100/40 He	18.5kW	1500 rpm	1300mm / 950mm / 950mm	1100 l/min	40 bar (580 psi)	3	3
SV 2400/40 He	37kW	1500 rpm	1570mm / 1080mm / 1120mm	2350 l/min	40 bar (580 psi)	3	4
SV 1101/80 He	18.5kW	1500 rpm	1300mm / 900mm / 950mm	1100 l/min	80 bar (1160 psi)	3	3
SVB 225/250 He	7.5kW	1500 rpm	920mm / 770mm / 650mm	225 l/min	250 bar (3626 psi)	3	3
SVC 450/350 He	15kW	1500 rpm	1195mm / 775mm/ 830mm	455 l/min	350 bar (5076 psi)	4	4
SVD 600/350 He	15kW	1500rpm	1205mm / 890mm / 925mm	575 l/min	350 bar (5076 psi)	4	4
SVD 700/350 He	22kW	1500rpm	1270mm / 890mm / 925mm	700 l/min	350 bar (5076 psi)	4	4
SVB 1100/350 He	30kW	1500rpm	1460mm / 1050mm / 1085mm	1080 l/min	350 bar (5076 psi)	4	4
SVB 1300/350 He	45kW	1500rpm	1580mm / 1080mm / 1150mm	1390 l/min	350 bar (5076 psi)	4	4