

Model	<u>GBTU-DLE2-1-GG</u>	<u>GBTU-DLE5-1-GG</u>	<u>GBTU-DLE15-1-GG</u>	<u>GBTU-DLE30-1-GG</u>	<u>GBTU-DLE75-1-GG</u>
Max Outlet Pressure	20 bar/ 290 psi	50 bar/ 725 psi	150 bar/ 2175 psi	300 bar/ 4350 psi	750 bar/ 10875 psi
Air Drive Pressure	1-10 bar / 14,5—145 psi	1-10 bar / 14,5—145 psi	1-10 bar / 14,5—145 psi	1-10 bar / 14,5—145 psi	1-10 bar / 14,5—145 psi
Pressure Ratio	1 : 2	1 : 5	1 : 15	1 : 30	1 : 75
Compression Ratio	1 : 10	1 : 15	1 :20	1 : 20	1 : 20
Displacement volume/stroke	922 cm3	373 cm3	122 cm3	60 cm3	25 cm3
Max Cycles	100 / min	110 / min	130 / min	130 / min	130 / min
Stall Pressure	PB = i * pL	PB = i * pL + pA	PB = i * pL + pA	PB = i * pL + pA	PB = i * pL + pA
Connections -					
Inlet:	1/2" BSP	1/2" BSP	1/4" BSP	1/4" BSP	1/4" BSP
Outlet:	1/2" BSP	1/2" BSP	1/4" BSP	1/4" BSP	1/4" BSP
Air:	3/4" BSP	3/4" BSP	3/4" BSP	3/4" BSP	3/4" BSP
Air Pressure Gauge	0-11bar / 160psi	0-11bar / 160psi	0-11bar / 160psi	0-11bar / 160psi	0-11bar / 160psi
Pressure Gauge	0-25bar / 362psi 100mm glycerine filled	0-60bar / 870psi 100mm glycerine filled	0-1724bar / 25000psi 100mm glycerine filled	0-50bar / 725psi 100mm glycerine filled	0-1000bar / 14500psi 100mm glycerine filled
Max Temp	60°C	60°C	100°C	100°C	100°C
Frame	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Compressor Head	Aluminium Anodised	Aluminium Anodised	1.4305	1.4305	1.4305
HP Cylinder	Aluminium hardcoated	1.4404	1.4542	1.4542	1.4542
Piston	1.4305 (hardened)	1.4305 (hardened)	1.4305 (hardened)	1.4305 (hardened)	1.4305 (hardened)
Valves Fittings & Tubing	316 ss	316 ss	316 ss	316 ss	316 ss
Seal Package -					
Inert Gas	PTFE, Viton	PTFE, Viton	PTFE, Viton	PTFE, Viton	PTFE, Viton
Oxygen	PTFE, Viton	PTFE, Viton	PTFE, Viton	PTFE, Viton	PTFE, Viton
Co2	PTFE, NBR	PTFE, NBR	PTFE, NBR	PTFE, NBR	PTFE, NBR
Overall Size	400w x 500h x 580d mm	400w x 500h x 580d mm	400w x 500h x 580d mm	400w x 500h x 580d mm	400w x 500h x 580d mm
Weight	27kg	27kg	27kg	27kg	27kg